



FrontRow ToGo – Take audio anywhere

Completely portable, FrontRow ToGo incorporates a DuO™ precision-mounted speaker array for amazingly even coverage of classrooms, cafeteria, meeting spaces — even outdoor venues.

FrontRow ToGo goes anywhere people need to listen. Its powerful rechargeable battery, collapsible stand, and optional carrying case let you talk or play music far from power sources. And with wind-resistant boom microphones and OptiVoice™ speech-clarifying technology, ToGo is as audible at a soccer meet or bus line as it is in a classroom.

FrontRow ToGo operates on the same radio band used by personal assistive listening systems for students with hearing impairment. Use a single transmitter on up to 16 different channels to communicate with both the ToGo and students' personal devices.

With the CMBT Bluetooth® audio receiver, teachers can wirelessly play audio for the entire class through their ToGo system. Now instructors can conveniently use audio from phones, TVs, tablets and other Bluetooth®-enabled devices to support their lessons.

KEY FEATURES

- Installation-free and completely portable — onboard rechargeable battery lasts hours
- Input jack for music and output jack for recording
- OptiVoice™ speech clarification
- Powerful two-driver line array for more even audio coverage than flat panels provide
- Great for pass-around at conferences, outdoor events and lectures
- Boom mic for excellent sound quality, indoors and out
- Optional CMBT Bluetooth® audio receiver to enable wireless connectivity

Receiver/Speaker Array

SPECIFICATIONS

Transmission type	FM (F3E)
Receiving frequency	216.025 - 216.875 MHz
Frequency response	100Hz-9kHz (at rated output)
THD	<1.5% (at rated output) @ 1kHz
Signal-to-noise	>70db at rated output (system)
Maximum audio output power	Maximum 36W RMS @ 4Ω x 2
Power supply	AC 110-220V ~50-60Hz, 1A max
Battery	NiMH rechargeable
Battery life	6.5 hours (rechargeable)
Recharging time	8 hours
Input	1 x aux-in, 3.5mm mono
Output	1 x aux-out, 3.5mm mono
User controls	Channel A/B on/off/volume, Channel A/B channel selector, aux-in volume, aux-out volume, OptiVoice™, main power
Size (wxdxh)	183 x 85 x 750 mm / 7.2 x 3.4 x 29.5 in
Weight	5.7kg /12.5lbs.



925T Body-Worn Transmitter

SPECIFICATIONS

Carrier frequency range	216.025 - 216.875 MHz
Modulation	FM (F3E)
Operating range	> 34m / 110ft
THD	<0.5%
Dynamic range	100dB
Size (wxhxd)	65 x 90 x 25 mm / 2.5 x 3.5 x 1 in
Weight	51g / 1.8oz
Controls	on/mute/off/channel selector
Input/output	2.5mm microphone input jack
Battery type	2 AA NiMH rechargeable (1600mA) or 2 AA alkaline disposable
Battery life	NiMH rechargeable typically 12 hours, disposable alkaline typically 15 hours
Recharging time	6 hours



925H Handheld Microphone/Transmitter

SPECIFICATIONS

Carrier frequency range	216.025 - 216.875 MHz
Modulation	FM (F3E)
Operating range	> 34m / 110ft
RF output	<15mW
THD	<0.5%
Dynamic range	100dB
Size (dia x h)	54 x 237mm / 2.1 x 9.3 in
Weight	230g / 8.1 oz
Controls	on/mute/off/channel selector
Battery type	2 AA NiMH rechargeable (1600mA) or 2 AA alkaline disposable
Battery life	12 hours (rechargeable), 15 hours (alkaline)
Recharging time	6 hours



925C Charging Stand

SPECIFICATIONS

Power supply	AC adaptor (DC 12V / 0.5A)
Recharging time	NiMH (1600mA), 6 hours
Size (wxhxd)	230 x 47 x 135 mm / 9 x 1.9 x 5.3 in
Weight	360g/12.7oz



Learn more at precision-acoustics.com.au



RevF 0920